

PLUS

Floor Finish & Cleaner/Maintainer



Low sheen acrylic finish with integrated cleaner/maintainer. Durable, wear-resistant coating. High solids (30%). Use as finish only or as one step solution for clean-maintain.



Item Numbers:
 33.8 Ounces (1 Liter) HD-P1L
 1.33 Gallon (5 Liter): HD-P133
 5 Gallons: HD-PLUS5G

Features

- One Step Clean & Low-Sheen Polish Solution
- Reduced strip & polish Cycles
- Excellent Wear & Scuff Resistance
- Unique blend of detergents, waxes & polymers
- Works with Spray Buff System

Flooring Types

- Sheet Vinyl
- Rubber
- LVT
- Marble
- VCT
- Linoleum
- Concrete
- Terrazzo
- Cork
- Slate
- Quarry Tile
- Asphalt Tile

Environments

- Healthcare
- Schools & Universities
- Institutional
- Office Buildings
- Residential

Additional Product Information

- Less strip & polish means less down-time and reduced maintenance costs.
- Rejuvenates gloss level with routine cleaning.
- No rinsing required after cleaning process.
- Only 2-3 coats required for initial application.
- Contributes to Environmentally Friendly Initiatives: Improved Indoor Air Quality & Reduced Water Usage.
- Sizes: 33.8 oz, 1.33 Gal, 5 Gal.

Directions for Use

Initial Application Coverage, Single coat (undiluted):

- 33.8 Ounces: 350 square feet depending on porosity of flooring material and application method.
- 1.33 Gallon: 1500-2000 square feet depending on porosity of flooring material and application method.
- 5 Gallons: 7500-10,000 square feet depending on porosity of flooring material and application method.

(2-3 coats required for Initial Application. See product label for detailed instructions.)

Initial Application Directions: Thoroughly clean floor or remove coating as applicable and rinse. Apply undiluted in 2-3 thin, even coats with a microfiber applicator mop. Air dry between coats and cure overnight. (See product label for detailed instructions.)

Routine Cleaning Directions: Dilute according to label instructions. Clean with a 2-bucket mop system or autoscrubber. Pick up excess solution. Do not rinse. Allow to air dry. (See product label for detailed instructions.)

Spray Buff Directions: Dilute according to label instructions. Use a white pad for buffing. (See product label for detailed instructions.)

Details

- Protect from freezing.
- Scuff & stain resistant finish.
- Safe for use on sensitive flooring types.
- 30% Solids content.
- Mild, pleasant fragrance.
- No VOCs.
- Exceptionally durable Acrylic finish.
- Non-Yellowing.



www.hilway.com
 1-877-356-6748

HD-P1L/P133/PLUS5G V2.1: 04-2016

Hilway Direct™
 12 McCullough Dr, ste 10
 New Castle, DE 19720