

PRIMO HP

Polyurethane-Acrylic Floor Finish

item no: HD-PRM1L, HD-PRM133



INSTRUCTIONS FOR USE & COVERAGE:

Initial Application Directions:

1. Dry sweep then damp mop floor to remove loose dirt and soil. Thoroughly clean floor with Hilway Direct Neutral Cleaner or Allsafe Stripper or flooring manufacturer's recommended product.
2. If flooring has a factory or site-applied acrylic coating, remove coating following flooring manufacturer's instructions. This usually can be done using Hilway Direct Allsafe Stripper diluted 1:5 or 1:10 with clean water, or flooring manufacturer's recommended product diluted as directed, in an auto scrubber or low rpm swing machine with a red scrub pad or equivalent. Always rinse and neutralize floor with clean water after removing old coating. Do not let stripper solution dry on floor.
3. Shake Hilway Direct Primo vigorously for 30 seconds then let it settle for 5 minutes. Floor must be completely dry before applying floor finish. Apply undiluted in a thin, even coat using a microfiber applicator mop. Do not use treated dust mops.
4. When first coat is dry enough to walk on (approx 1 hour), apply second coat crosswise.
5. Allow floor surface to cure minimum 12 hours before allowing traffic on floor. Dry times will vary depending upon ambient temperature and humidity.

Daily Cleaning, Mop & Bucket or Auto Scrub Machine:

1. Sweep floor to remove loose dirt & soil.
2. Using Mop & Bucket (2-bucket system) or Auto-Scrub Machine, dilute Hilway Direct Neutral Cleaner as directed on product label. Mop floor with the cleaning solution.
3. Pick up soil and excess solution with a clean, tightly wrung out mop. For autoscrubber, trail mop excessive wet areas behind scrubber.
5. Do not rinse after cleaning.
6. Allow to air dry completely.

For Use On: Sheet Vinyl, LVT, VCT, Rubber, Linoleum, Cork, Asphalt Tile, Marble, Slate, Concrete, Quarry Tile, or Terrazzo flooring. Prior to use always test in a small inconspicuous area to check for good adhesion and desired result.

Caution: Eye irritant. Avoid contact with skin and eyes. Do not taste or swallow. In case of contact with eyes or skin flush with plenty of water. If irritation develops, seek medical attention. In case of ingestion, flush mouth with water, drink large quantities of water and seek immediate medical attention, DO NOT induce vomiting. KEEP OUT OF REACH OF CHILDREN.

Note: Avoid solution contact with sensitive surfaces such as wood, metal, furnishings. When applying finish avoid strong sunlight and drafts. Turn off under floor heat prior to application. Read full MSDS (available for download: www.hilway.com) and product label prior to use.

Handling and Storage: Protect from freezing. Recommended storage temperature: 68°F (20°C). Do not store near food.

Initial Application Coverage, Single coat (undiluted):

- HD-PRM1L, 1 Liter (33.8 oz): 350 sq. ft./ Liter. Coverage may vary depending on porosity of flooring material.
- HD-PRM133, 1.33 Gallons: 1500-2000 sq. ft./Gallon. Coverage may vary depending on porosity of flooring material.
(2-3 coats required for Initial Application.)



www.hilway.com
1-877-356-6748

INSTR HD-PRM1L/PRM133 V2: 07-2014

Hilway Direct™
12 McCullough Dr, ste 10
New Castle, DE 19720