

SATIN Floor Finish



Enhancing low sheen finish. Durable, highly scuff-resistant, protective coating. High solids (30%) acrylic finish. Use on resilient and hard surface floors.



Item Numbers:

1 Liter (33.8 oz): HD-S1L

1.33 Gallon: HD-S133

Features

- Satin Acrylic Finish.
- High Solids Content (30%) for dependable Durability.
- Excellent Wear & Scuff Resistance.
- No VOCs.
- Non-Yellowing.

Flooring Types

- Sheet Vinyl
- Rubber
- LVT
- Marble
- VCT
- Linoleum
- Concrete
- Terrazzo
- Cork
- Slate
- Quarry Tile
- Asphalt Tile

Environments

- Healthcare
- Schools & Universities
- Institutional
- Office Buildings
- Residential

Additional Product Information

- Gloss Level: 18 (based on Gloss Scale)
- Safe for use on sensitive flooring types.
- Only 2-3 coats required for initial application.
- Cleans routinely with Hilway Direct Neutral Cleaner.
- Non-hazardous, no VOCs.
- Exceptionally durable Acrylic finish.
- Sizes: 1 Liter (33.8 oz), 1.33 Gallons.

Directions for Use

Initial Application Coverage, Single coat (undiluted):

- 1 Liter (33.8 oz): 350 square feet depending on porosity of flooring material.
- 1.33 Gallons: 1500-2000 square feet depending on porosity of flooring material.

(2-3 coats required for Initial Application. See product label for detailed instructions.)

Application Directions:

Remove loose dirt and soil. Thoroughly clean floor or remove coating as applicable. Rinse and neutralize floor with clean water. Apply Hilway Direct Satin undiluted in a thin, even coat using a microfiber applicator mop. Apply 2-3 coats. Allow each coat to air dry completely (generally 30-60 minutes) before applying next coat. Allow floor surface to dry overnight before heavy traffic use. (See product label for detailed instructions.)

Details

- Satin Acrylic finish enhances floor's appearance.
- 30% Solids content.
- Scuff & stain resistant finish.
- Safe for use on sensitive flooring types.
- Exceptionally durable Acrylic finish.
- Non-hazardous, VOC free.
- Non-Yellowing.



www.hilway.com
1-877-356-6748

HD-S1L/S133V2: 07-2014

Hilway Direct™
12 McCullough Dr, ste 10
New Castle, DE 19720