

MATTE / SATIN

Acrylic Floor Finish

Items HD-M1L, HD-M133, HD-S1L, HD-S133

Instructions for Use:

Initial Application

1. Dry sweep then damp mop floor to remove loose dirt and soil. Thoroughly clean floor with Hilway Direct Neutral Cleaner or Allsafe Stripper or flooring manufacturer's recommended product.
2. If flooring has a factory or site-applied acrylic coating, remove coating following flooring manufacturer's instructions. This usually can be done using Hilway Direct Allsafe Stripper diluted 1:5 or 1:10 with water, or use flooring manufacturer's recommended product diluted as directed, in an auto scrubber or with a low rpm swing machine equipped with a red scrub pad or equivalent. Always rinse and neutralize floor with clean water after removing old coating. Do not let stripper solution dry on floor.
3. Shake product vigorously for 30 seconds then let it settle for 5 minutes. Apply undiluted in a thin, even coat using a microfiber applicator mop. Do not use treated dust mops.
4. Apply 2-3 coats. Allow each coat to air dry completely (generally 30-60 minutes) before applying next coat.
5. Allow floor surface to cure overnight before heavy traffic use. Dry times will vary depending upon ambient temperature and humidity.

For Use On

Vinyl/Luxury sheet-plank-tile (LVT/LVP), VCT, PVC, Non-PVC, Rubber, Linoleum, Cork, Asphalt Tile, Marble, Slate, Concrete, Quarry Tile, Terrazzo. Prior to use always test in a small inconspicuous area to check for good adhesion and desired result. Contact manufacturer for specific applications, floor brands & floor types not mentioned here. Testing has been conducted on some flooring brands.

Caution

Eye irritant. Avoid contact with skin and eyes. Do not taste or swallow. In case of contact with eyes or skin flush with plenty of water. If irritation develops, seek medical attention. In case of ingestion, flush mouth with water, drink large quantities of water and seek immediate medical attention, DO NOT induce vomiting. KEEP OUT OF REACH OF CHILDREN.

Additional Instructions

Avoid solution contact with sensitive surfaces such as wood, metal, furnishings. When applying finish avoid strong sunlight and drafts. Turn off under floor heat prior to application. Read full SDS (available for download: www.hilway.com) and product label prior to use.

Handling and Storage

Protect from freezing. NOT freeze-thaw stable. Recommended storage temperature: 68°F (20°C). Do not store near food. Shelf life is approximately 2 years.

Initial Application Coverage, Single coat (undiluted)

- 33.8 Ounces: approximately 350 square feet
- 1.33 Gallon: 1500-2000 square feet

Note: 2 – 3 coats required.

Routine Cleaning:

Use **Hilway Direct Neutral Cleaner** with mop & bucket, auto scrub machine, or spray & flat mop.
See *cleaner instructions, information, SDS, and product label for additional information.*

Finish Removal & Heavy Duty Cleaning:

Use **Hilway Direct AllSafe Stripper** with mop & bucket or auto scrub machine.
See *Allsafe Stripper instructions, information, SDS, and product label for additional information.*