

# ALLSAFE STRIPPER

## Floor Finish Remover

Items HD-NC1L, HD-NC133

### Instructions for Use:

#### Cleaning After Installation / Heavy-duty Cleaning:

1. Following flooring manufacturer instructions for wait time before first cleaning a newly installed floor.
2. Sweep, or vacuum on hard floor setting, to remove loose dirt and soil from floor.
3. Dilute Stripper with water in a ratio of between 1:5 and 1:10. *In case of particularly stubborn residue (e.g., in the commercial sector) use undiluted if required. For low levels of dirt increase the amount of water accordingly.*
4. Apply the cleaning solution to the floor. Distribute and allow to stand for approx 10 minutes, then agitate the flooring surface with a red scrub pad or scrubbing brush on an automatic scrubber. **Do not allow solution to dry on floor.** Blue or green scrub pad can be used for more aggressive cleaning needs however be aware that these pads are not appropriate for some floor types including LVT, rubber and linoleum. Manual scrubbing is also an option, using red pad or white brush for LVT, rubber and linoleum floors.
5. Pick up dirty solution with wet-dry vacuum or trail mop.
6. Rinse floor thoroughly.
7. Allow floor to air dry.

#### Stripping / Removing Finish:

1. Sweep, or vacuum on hard floor setting, to remove loose dirt and soil from floor.
2. Apply Allsafe Stripper to floor undiluted or diluted 1:3 with water for commercial applications; 1:5 with water for residential applications.
3. Spray the floor with clear water then apply the stripping solution to the floor.
4. Distribute solution and allow it to stand for 10-20 minutes then agitate the flooring surface with a red, blue or green pad or scrubbing brush on an automatic scrubber. For manual application, use a standard mop and scrub pad or brush. **Do not allow solution to dry on floor.** For sensitive flooring surfaces, dilute Allsafe Stripper 1:5 to 1:10 and apply several times with shorter stand times. Sensitive flooring surfaces should be tested in an inconspicuous area prior to full use. Use red pad or white brush only on LVT, rubber and linoleum floors.
5. Pick up dirty solution with wet-dry vacuum or mop and follow with clean water rinse.
6. Allow floor to dry completely.

#### For Use On

Sheet Vinyl, LVT, VCT, Rubber, Linoleum, PVC, Non-PVC, Cork, Asphalt Tile, Marble, Slate, Concrete, Quarry Tile, or Terrazzo flooring. Use to remove acrylic floor finishes including Hilway Direct Plus and Primo. Prior to use always test in a small inconspicuous area to check for compatibility and desired result.

#### Caution

Eye irritant. Avoid contact with skin and eyes. Do not taste or swallow. In case of contact with eyes or skin flush with plenty of water. If irritation develops, seek medical attention. In case of ingestion, flush mouth with water, drink large quantities of water and seek immediate medical attention, DO NOT induce vomiting. KEEP OUT OF REACH OF CHILDREN. Use in a well ventilated area.

#### Additional Instructions

A wet floor is slippery. Use caution signage to prevent traffic on floor while it is wet. Read full SDS (available for download: [www.hilway.com](http://www.hilway.com)) and product label prior to use. Some floors will be slippery without a finish applied to the floor. Keep traffic off of these floor types until they are coated with an appropriate floor finish.

#### Handling and Storage

Freeze-thaw stable however recommended storage is at: 68°F (20°C). Do not store near food. Shelf life is approximately 2 years.

#### Coverage

- 33.8 Ounces: 200 square feet or more depending on dilution ratio
- 1.33 Gallon: 1000 square feet or more depending on dilution ratio