

PRIMO GLOSS

Polyurethane-Acrylic Floor Finish

Items HD-PRMG1L, HD-PRMG133

Extremely hard-wearing high gloss polyurethane-acrylic blend floor finish. High solids (42%). Optimal in high traffic areas where high gloss finish is required. Can be removed and reapplied as needed. Works well in a spray-buff program.



Features

- Heavy-duty floor finish for high traffic facilities
- More durable than acrylic only floor finishes
- Performs well in a spray-buff program
- High-shine finish
- Typical floor finish application process
- Scrub and recoat as needed

Floor Types *(For specific application inquiries, contact manufacturer.)*

- *Luxury Vinyl
- Rubber
- VCT
- PVC / Non-PVC
- Sheet Vinyl
- Linoleum
- Quarry Tile
- Most Resilient Floors

**High-gloss not recommended for luxury vinyl floors that mimic natural wood or stone.*

Facilities

- Healthcare
- Corporate
- Institutional
- Schools / Universities
- Retail
- Multi-family Housing

Items:

HD-PRMG1L

1-Liter (33.8 Ounces)
coverage: approx 350 sq ft

HD-PRMG133

5-Liter (1.33 Gallons)
coverage: 1500 - 2000 sq ft

Product Information

- Scuff & stain resistant floor finish.
- Very high solids content.
- Only 2 coats required for initial application.
- Contributes to improved indoor air quality.
- High-gloss shine.
- Sizes: 33.8 oz, 1.33 gal.
- Responds well to spray buffing.
- Clean routinely with Hilway Direct Neutral Cleaner.

Directions for Use *(See instructions sheet and/or product label for detailed instructions.)*

Initial Application: Remove loose dirt and soil. Thoroughly clean floor or remove coating as applicable and rinse with clean water to neutralize. Apply undiluted in a thin, even coat using a microfiber applicator mop. Allow to air dry completely (approximately 60 minutes) before applying 2nd coat crosswise. Allow floor surface to dry minimum 12 hours before heavy traffic use.

Spray Buff: Dilute according to label instructions. Use a white pad for buffing.

Details

- Protect from freezing.
- Acrylic-modified polyurethane finish.
- For use in high-traffic facilities.
- Excellent stain & scuff resistance.
- *High-gloss.
- Only 2 initial coats required.
- Floor ready for use in 12 hours.
- No VOCs.
- Shelf Life: 2 years.

**High-gloss finishes tend to show floor imperfections more than low-gloss & matte finishes.*

Hilway Direct products available for purchase at 1877floorguy.com or request quote: (877)356-6748 or help@1877floorguy.com.