

PRIMO HP

Polyurethane-Acrylic Floor Finish

Items HD-PRM1L, HD-PRM133

Extremely hard-wearing low sheen polyurethane-acrylic blend floor finish. High solids (42%). Optimal in high traffic areas. Can be removed and reapplied as needed. Works well in a spray-buff program.



Features

- Heavy-duty floor finish for high traffic facilities
- More durable than acrylic only floor finishes
- Performs well in a spray-buff program
- Low-sheen
- Typical floor finish application process
- Scrub and recoat as needed

Floor Types

(For specific application inquiries, contact manufacturer.)

- LVT / LVP
- Rubber
- VCT
- PVC / Non-PVC
- Sheet Vinyl
- Linoleum
- Quarry Tile
- Most Resilient Floors

Facilities

- Healthcare
- Corporate
- Institutional
- Schools / Universities
- Retail
- Multi-family Housing

Items:

HD-PRM1L

1-Liter (33.8 Ounces)
coverage: approx 350 sq ft

HD-PRM133

5-Liter (1.33 Gallons)
coverage: 1500 - 2000 sq ft

Product Information

- Polyurethane-Acrylic blend.
- Low-gloss sheen.
- Excellent scuff & scratch resistance.
- Very high solids content provides increased durability.
- Only 2 coats required for initial application.
- Contributes to improved indoor air quality.
- Sizes: 33.8 oz, 1.33 gal.
- Responds well to spray buffing.

Directions for Use

(See instructions sheet and/or product label for detailed instructions.)

Initial Application: Remove loose dirt and soil. Thoroughly clean floor or remove coating as applicable and rinse with clean water to neutralize. Apply undiluted in a thin, even coat using a microfiber applicator mop. Allow to air dry completely (approximately 60 minutes) before applying 2nd coat crosswise. Allow floor surface to dry minimum 12 hours before heavy traffic use.

Spray Buff: Dilute according to label instructions. Use a white pad for buffing.

Routine Cleaning: Clean with Hilway Direct Neutral Cleaner.

Details

- Protect from freezing.
- Acrylic-modified polyurethane finish.
- For use in high-traffic facilities.
- Excellent stain & scuff resistance.
- Low-sheen finish.
- Only 2 initial coats required.
- Floor ready for use in 12 hours.
- No VOCs.
- Shelf Life: 2 years.

Hilway Direct products available for purchase at 1877floorguy.com or request quote: (877)356-6748 or help@1877floorguy.com.