

# ALLSAFE STRIPPER



item no: HD-AS1L, HD-AS133

## INSTRUCTIONS FOR USE & COVERAGE:

### Cleaning After Installation:

1. Sweep or vacuum to remove loose dirt and soil from floor.
2. For stubborn dirt, dilute Hilway Direct Allsafe Stripper 1:5 (1/2 oz stripper to 10oz water) or 1:10 (1oz stripper to 10oz water). In case of stubborn residues, apply undiluted as necessary. In case of only slight soiling, adjust dilution ratio accordingly.
3. Distribute solution over floor and allow to stand for approximately 10 minutes then agitate the flooring surface with a red scrub pad or scrubbing brush on an automatic scrubber. For manual application, use a standard mop and scrub brush. Do not allow solution to dry on floor.
4. Pick up dirty solution with wet-dry vacuum or mop and follow with clean water rinse.
5. Allow floor to air dry.

### Stripping/Removing Finish:

1. Sweep or vacuum to remove loose dirt and soil from floor.
2. Apply Allsafe Stripper to floor undiluted and allow to stand for 15-20 minutes then agitate the flooring surface with a blue or green pad or scrubbing brush on an automatic scrubber. For manual application, use a standard mop and scrub brush. Do not allow solution to dry on floor. For sensitive flooring surfaces, if necessary, dilute Allsafe Stripper and apply several times with shorter stand times. (Sensitive surfaces should be tested in an inconspicuous area prior to full use.)
3. Pick up dirty solution with wet-dry vacuum or mop and follow with clean water rinse.
4. Allow floor to air dry.

**For Use On:** Sheet Vinyl, LVT, VCT, Rubber, Linoleum, Cork, Asphalt Tile, Marble, Slate, Concrete, Quarry Tile, or Terrazzo flooring that has been sealed with an acrylic finish. Prior to use always test in a small inconspicuous area to check for compatibility and desired result.

**Caution:** Eye irritant. Avoid contact with skin and eyes. Do not taste or swallow. In case of contact with eyes or skin flush with plenty of water. If irritation develops, seek medical attention. In case of ingestion, flush mouth with water, drink large quantities of water and seek immediate medical attention, DO NOT induce vomiting. **KEEP OUT OF REACH OF CHILDREN.**

**Handling and Storage:** Protect from freezing. Recommended storage temperature: 68°F (20°C). Avoid storing in direct sunlight and high temperatures. Do not store near food.

**Notes:** During use, wear rubber gloves and ensure work area is well ventilated. Avoid solution contact with sensitive surfaces such as wood, metal, furnishings. Read full MSDS (available for download: [www.hilway.com](http://www.hilway.com)) and product label prior to use. For sensitive flooring surfaces, test prior to full use. A stripped floor is slippery. Use caution signage to prevent traffic on stripped floor until flooring finish is applied and properly cured. Slip-resistant footwear is recommended for individuals who need to walk on the stripped floor and for those applying stripping solution to floor.

### Coverage:

- HD-AS1L, 1 Liter (33.8 oz): Approximately 200 sq. ft./ Liter. Coverage will depend on dilution rate.
- HD-AS133, 1.33 Gallons: Approximately 1000 sq. ft./ Gallon. Coverage will depend on dilution rate.



[www.hilway.com](http://www.hilway.com)  
1-877-356-6748

INSTR HD-AS1L/AS133 V2: 07-2014

**Hilway Direct™**  
12 McCullough Dr, ste 10  
New Castle, DE 19720