

# NEUTRAL CLEANER



item no: HD-NC1L, HD-NC133

## INSTRUCTIONS FOR USE & COVERAGE:

### Cleaning After Installation Directions:

1. Sweep or vacuum to remove loose dirt and soil from floor.
2. For stubborn dirt, dilute Hilway Direct Neutral Cleaner 1:10 (1oz cleaner to 10oz water). Reduce concentration accordingly for slightly soiled floors.
3. Distribute cleaning solution over floor and allow to stand for a short time (approx 10-20 minutes) then agitate the flooring surface with a red scrub pad or scrubbing brush on an automatic scrubber. Do not allow solution to dry on floor.
4. Pick up dirty solution with wet-dry vacuum or mop and follow with clean water rinse.
5. Allow floor to air dry.

### Routine/Daily Cleaning Directions:

1. Sweep or vacuum to remove loose dirt and soil from floor.
2. Dilute Hilway Direct Neutral Cleaner 1:200 (1/2 oz cleaner to 1 gallon water) for Mop & Bucket (use 2-bucket system) or 1:400 (1/4 oz cleaner to 1 gallon water) for Automatic Scrubber.
3. Mop floor with the cleaning solution.
4. Trail mop excess soil and wet areas with a clean, tightly wrung out mop.
5. No rinsing required.
6. Allow floor to air dry completely.

**For Use On:** Sheet Vinyl, LVT, VCT, Rubber, Linoleum, Cork, Asphalt Tile, Marble, Slate, Concrete, Quarry Tile, or Terrazzo flooring that has been sealed with an acrylic finish.

**Caution:** Eye irritant. Avoid contact with skin and eyes. Do not taste or swallow. In case of contact with eyes or skin flush with plenty of water. If irritation develops, seek medical attention. In case of ingestion, flush mouth with water, drink large quantities of water and seek immediate medical attention, DO NOT induce vomiting. **KEEP OUT OF REACH OF CHILDREN.**

**Handling and Storage:** Protect from freezing. Recommended storage temperature: 68°F (20°C). Avoid storing in direct sunlight and high temperatures. Do not store near food.

**Notes:** Avoid solution contact with sensitive surfaces such as wood, metal, furnishings. Read full MSDS (available for download: [www.hilway.com](http://www.hilway.com)) and product label prior to use. A wet floor is slippery. Use caution signage to prevent traffic on floor while it is wet.

### Coverage:

- HD-NC1L, 1 Liter (33.8 oz): Approximately 10,000 sq. ft./ Liter. Coverage will depend on dilution rate.
- HD-NC133, 1.33 Gallons: Approximately 52,000 sq. ft./ Gallon. Coverage will depend on dilution rate.



[www.hilway.com](http://www.hilway.com)  
1-877-356-6748

INSTR HD-NC1L/NC133 V2: 07-2014

**Hilway Direct™**  
12 McCullough Dr, ste 10  
New Castle, DE 19720