

PRIMO HP

Polyurethane-Acrylic Floor Finish



Extremely hard-wearing acrylic modified polyurethane finish. Optimal high traffic performance. Low sheen. Scuff-resistant. Use on resilient and hard surface floors.



Item Numbers:
1 Liter (33.8 oz): HD-PRM1L
1.33 Gallon: HD-PRM133

Features

- High (42%) Solids Content
- Specially formulated Polyurethane-Acrylic Blend
- Extremely hard-wearing in high traffic areas
- Low-Sheen
- Scuff Resistant

Flooring Types

- Sheet Vinyl
- Rubber
- LVT
- Marble
- VCT
- Linoleum
- Concrete
- Terrazzo
- Cork
- Slate
- Quarry Tile
- Asphalt Tile

Environments

- Healthcare
- Schools & Universities
- Institutional
- Office Buildings
- Residential

Additional Product Information

- Low-Gloss Level.
- Scuff & stain resistant finish.
- Safe for use on sensitive flooring types.
- Optimal Performance in High-Traffic Areas.
- Only 2 coats required.
- Non-hazardous, no VOCs.
- Cleans routinely with Hilway Direct Neutral Cleaner.
- Sizes: 1 Liter (33.8 oz), 1.33 Gallons.

Directions for Use

Initial Application Coverage, Single coat (undiluted):

- 1 Liter (33.8 oz): 350 square feet depending on porosity of flooring material.
 - 1.33 Gallons: 1500-2000 square feet depending on porosity of flooring material.
- (2 coats required for Initial Application. See product label for detailed instructions.)

Application Directions:

Remove loose dirt and soil. Thoroughly clean floor or remove coating as applicable. Rinse and neutralize floor with clean water. Apply Hilway Direct Primo undiluted in a thin, even coat using a microfiber applicator mop. Allow to air dry completely (approximately 60 minutes) before applying 2nd coat crosswise. Allow floor surface to dry minimum 12 hours before heavy traffic use. (See product label for detailed instructions.)

Details

- Acrylic-modified Polyurethane.
- Extremely durable Finish.
- For Use in High-Traffic Areas.
- Scuff & stain resistant.
- Only 2 coats required.
- Safe for use on sensitive flooring types.
- Cleans routinely with Hilway Direct Neutral Cleaner.



www.hilway.com
1-877-356-6748

HD-PRM1L/PRM133 V2: 07-2014

Hilway Direct™
12 McCullough Dr, ste 10
New Castle, DE 19720